

US009636797B2

(12) United States Patent

Xu et al.

(10) Patent No.: US 9,636,797 B2

(45) **Date of Patent:**

May 2, 2017

(54) ADJUSTING EDDY CURRENT MEASUREMENTS

(71) Applicant: **Applied Materials, Inc.**, Santa Clara, CA (US)

(72) Inventors: Kun Xu, Sunol, CA (US); Ingemar Carlsson, Milpitas, CA (US); Boguslaw

A. Swedek, Cupertino, CA (US); Doyle E. Bennett, Santa Clara, CA (US); Shih-Haur Shen, Sunnyvale, CA (US); Hassan G Iravani, San Jose, CA (US); Wen-Chiang Tu, Mountain View, CA (US); Tzu-Yu Liu, San Jose, CA (US)

(73) Assignee: **Applied Materials, Inc.**, Santa Clara, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 537 days.

(21) Appl. No.: 14/179,297

(22) Filed: Feb. 12, 2014

(65) Prior Publication Data

US 2015/0224623 A1 Aug. 13, 2015

(51) **Int. Cl. B24B 49/10** (2006.01) **B24B 49/14** (2006.01)

(Continued)

(52) **U.S. CI.**CPC *B24B 49/105* (2013.01); *B24B 37/013* (2013.01); *B24B 49/02* (2013.01); *B24B 49/14* (2013.01)

(58) **Field of Classification Search**CPC B24B 37/013; B24B 49/02; B24B 49/105;
B24B 49/14; G01B 7/105; H01L

21/67253

(Continued)

(56) References Cited

U.S. PATENT DOCUMENTS

6,724,187 B2* 4/2004 Nix G01D 3/036 324/225

6,924,641 B1 8/2005 Hanawa et al.

(Continued)

FOREIGN PATENT DOCUMENTS

JP 2009-099842 5/2009 JP 2011-023579 2/2011 (Continued)

OTHER PUBLICATIONS

International Search Report and Written Opinion in International Application No. PCT/US2015/012281, dated Apr. 30, 2015, 5 pages.

Primary Examiner — Monica Carter Assistant Examiner — Marcel Dion (74) Attorney, Agent, or Firm — Fish & Richardson P.C.

(57) ABSTRACT

Among other things, a method of controlling polishing during a polishing process is described. The method includes receiving a measurement of a thickness, thick(t), of a conductive layer of a substrate undergoing polishing from an in-situ monitoring system at a time t; receiving a measured temperature, T(t), associated with the conductive layer at the time t; calculating resistivity ρ_T of the conductive layer at the measured temperature T(t); adjusting the measurement of the thickness using the calculated resistivity ρ_T to generate an adjusted measured thickness; and detecting a polishing endpoint or an adjustment for a polishing parameter based on the adjusted measured thickness.

19 Claims, 7 Drawing Sheets

